

Caps/Grommets/Connectors

Vinyl Vacuum Caps

- RoHS Compliant.
- Continuous Operating Temperature: -5°C (-22°F) to 148°C (300°F).
- Material: Vinyl.
- Length: 1/2" (for 1/8" & 3/16").
- Length: 3/4" (for 1/4", 5/16", 3/8", 1/2").



JT&T's Vinyl Vacuum Caps are resistant to tearing, cracking or splitting. The flexible design allows for stretching onto larger dimensions for a snug fit. Ideal for capping irregularly shaped objects. Flexible vinyl tip & round grip to provide a secure fit on your product. Can be used for capping lines & hoses while testing carburetors, emission control systems & vacuum lines. Commonly used to protect bolts, screws, threaded & non-threaded tubes, handles, covers, steel tubing, paint masks & to tightly cap off any un-used vacuum ports.

Part#	Ordering Size	Color	Pcs	Inner Diameter		Fits Tube Outer Diameter		Length Dimensions		Wall Thickness	
4800H	1/8"	Black	25	1/8" (.125")	3.18mm	3/16" (.188")	4.78mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4800L	1/8"	Black	50	1/8" (.125")	3.18mm	3/16" (.188")	4.78mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4800C	1/8"	Black	100	1/8" (.125")	3.18mm	3/16" (.188")	4.78mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801H	3/16"	Black	18	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801L	3/16"	Black	50	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801C	3/16"	Black	100	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801-9H	3/16"	White	18	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801-9L	3/16"	White	50	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4801-9C	3/16"	White	100	3/16" (.188")	4.78mm	1/4" (.250")	6.35mm	1/2" (.500")	12.70mm	(.040 +/- .010")	(1.02 +/- 0.25mm)
4802H	1/4"	Black	18	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4802L	1/4"	Black	50	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4802C	1/4"	Black	100	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4802-2H	1/4"	Red	18	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4802-2L	1/4"	Red	50	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4802-2C	1/4"	Red	100	1/4" (.250")	6.35mm	5/16" (.312")	7.92mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803H	5/16"	Black	15	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803L	5/16"	Black	50	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803C	5/16"	Black	100	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803-6H	5/16"	Blue	15	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803-6L	5/16"	Blue	50	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4803-6C	5/16"	Blue	100	5/16" (.312")	7.92mm	3/8" (.375")	9.52mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804H	3/8"	Black	10	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804L	3/8"	Black	50	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804C	3/8"	Black	100	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804-7H	3/8"	Yellow	10	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804-7L	3/8"	Yellow	50	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4804-7C	3/8"	Yellow	100	3/8" (.375")	9.52mm	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4806H	1/2"	Black	5	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4806L	1/2"	Black	50	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)
4806C	1/2"	Black	100	1/2" (.500")	12.70mm	3/4" (.750")	19.05mm	3/4" (.750")	19.05mm	(.065 +/- .010")	(1.65 +/- 0.25mm)

4805H - Assorted Black Vinyl Vacuum Caps | 30 Pcs.

- Continuous Operating Temperature: -5°C (-22°F) to 148°C (300°F).
- 1/8" thru 1/2" Inner Diameter.
- Length: 1/2" (for 1/8" & 3/16").
- Length: 3/4" (for 1/4", 5/16", 3/8", 1/2").

Part#	Description	Pcs
4800	1/8" I.D. Black Vinyl Vacuum Caps	7
4801	3/16" I.D. Black Vinyl Vacuum Caps	7
4802	1/4" I.D. Black Vinyl Vacuum Caps	4
4803	5/16" I.D. Black Vinyl Vacuum Caps	4
4804	3/8" I.D. Black Vinyl Vacuum Caps	4
4806	1/2" I.D. Black Vinyl Vacuum Caps	4

Kit is in a re-closable container.

**4805F-1 - Assorted Rainbow Vinyl Vacuum Caps | 35 Pcs.**

- Continuous Operating Temperature: -5°C (-22°F) to 148°C (300°F).
- 1/8" thru 3/8" Inner Diameter.
- Length: 1/2" (for 1/8" & 3/16").
- Length: 3/4" (for 1/4", 5/16", 3/8").

Part#	Description	Pcs
4800	1/8" I.D. Black Vinyl Vacuum Caps	9
4801-9	3/16" I.D. White Vinyl Vacuum Caps	8
4802-2	1/4" I.D. Red Vinyl Vacuum Caps	8
4803-6	5/16" I.D. Blue Vinyl Vacuum Caps	5
4804-7	3/8" I.D. Yellow Vinyl Vacuum Caps	5

Kit is in a re-closable container.

**4805F - Assorted Rainbow Vinyl Vacuum Caps | 50 Pcs.**

- Continuous Operating Temperature: -5°C (-22°F) to 148°C (300°F).
- 1/8" thru 3/8" Inner Diameter.
- Length: 1/2" (for 1/8" & 3/16").
- Length: 3/4" (for 1/4", 5/16", 3/8").

Part#	Description	Pcs
4800	1/8" I.D. Black Vinyl Vacuum Caps	5
4801	3/16" I.D. Black Vinyl Vacuum Caps	5
4801-9	3/16" I.D. White Vinyl Vacuum Caps	8
4802	1/4" I.D. Black Vinyl Vacuum Caps	4
4802-2	1/4" I.D. Red Vinyl Vacuum Caps	8
4803	5/16" I.D. Black Vinyl Vacuum Caps	4
4803-6	5/16" I.D. Blue Vinyl Vacuum Caps	6
4804	3/8" I.D. Black Vinyl Vacuum Caps	4
4804-7	3/8" I.D. Yellow Vinyl Vacuum Caps	6

Kit is in a re-closable container.

**4815F - Assorted Black Rubber Vacuum Caps | 20 Pcs.**

- Continuous Operating Temperature: -40°C (-40°F) to 160°C (320°F).
- 1/8" thru 3/8" Inner Diameter.
- Length: 9/16" (for 1/8", 3/16" 1/4").
- Length: 1-1/2" (for 3/8").

Part#	Description	Pcs
4810	1/8" I.D. Black Rubber Vacuum Caps	4
4811	3/16" I.D. Black Rubber Vacuum Caps	7
4812	1/4" I.D. Black Rubber Vacuum Caps	7
4813	3/8" I.D. Black Rubber Vacuum Caps	2

Kit is in a re-closable container.



Caps/Grommets/Connectors

Rubber Vacuum Caps

- Meets requirements of SAE-J200 & ASTM-D200 (formerly SAE-J114 & ASTM-D735), Class CE.
- RoHS Compliant.
- Continuous Operating Temperature: -40°C (-40°F) to 160°C (320°F).
- Material: Hypalon Rubber (Chlorosulfonated Polyethylene).
- Length: 9/16" (for 1/8", 3/16", 1/4").
- Length: 1-1/2" (for 3/8").



JT&T's Hypalon (CSM) Rubber Vacuum Caps are resistant to tearing, cracking or splitting. Hypalon has outstanding resistance to most chemicals (acids & alkalies), heat, ozone & oil which are among the most important characteristics. Hypalon is flame resistant, offers excellent color stability, weather & abrasion resistance. Low moisture absorption, good dielectric qualities & high abrasion resistance are among its other features. Like most synthetics hypalon is superior to natural rubber in temperature, oil & resistance to the effect of ozone. Hypalon is generally attacked by concentrated oxidizing acids, esters, ketones, chlorinated, aromatic & nitro hydrocarbons. Fair resistance to petroleum-based fluids. Similar to neoprene with improved acid resistance. Round grip to provide a secure fit on your product. Can be used for capping lines & hoses while testing carburetors, emission control systems & vacuum lines. Commonly used to protect bolts, screws, threaded & non-threaded tubes, handles, covers, steel tubing, paint masks & to tightly cap off any un-used vacuum ports.

Part#	Ordering Size	Color	Pcs	Inner Diameter Fits Tube Outer Diameter		Inside Length Dimensions			Wall Thickness		
4810H	1/8"	Black	3	1/8"	(.125")	3.18mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4810	1/8"	Black	50	1/8"	(.125")	3.18mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4810C	1/8"	Black	100	1/8"	(.125")	3.18mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4811H	3/16"	Black	3	3/16"	(.188")	4.78mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4811	3/16"	Black	50	3/16"	(.188")	4.78mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4811C	3/16"	Black	100	3/16"	(.188")	4.78mm	9/16"	(.562")	14.27mm	(.080 +/- .010")	(2.03 +/- 0.25mm)
4812H	1/4"	Black	3	1/4"	(.250")	6.35mm	9/16"	(.562")	14.27mm	(.100 +/- .010")	(2.54 +/- 0.25mm)
4812	1/4"	Black	50	1/4"	(.250")	6.35mm	9/16"	(.562")	14.27mm	(.100 +/- .010")	(2.54 +/- 0.25mm)
4812C	1/4"	Black	100	1/4"	(.250")	6.35mm	9/16"	(.562")	14.27mm	(.100 +/- .010")	(2.54 +/- 0.25mm)
4813H	3/8"	Black	2	3/8"	(.375")	9.52mm	1-1/2"	(1.50")	38.10mm	(.100 +/- .010")	(2.54 +/- 0.25mm)
4813	3/8"	Black	50	3/8"	(.375")	9.52mm	1-1/2"	(1.50")	38.10mm	(.100 +/- .010")	(2.54 +/- 0.25mm)
4813C	3/8"	Black	100	3/8"	(.375")	9.52mm	1-1/2"	(1.50")	38.10mm	(.100 +/- .010")	(2.54 +/- 0.25mm)

Need Primary Wire?

We have primary wire in a complete range of colors, gauges and lengths.

See our full line of wire and cable products starting on page 33.



Nylon Vacuum Connectors

- Continuous Operating Temperature: -40°C (-40°F) to 121°C (250°F).
- O.D. of Connector Fits I.D. of Vacuum Line Hose.
- Material: High Impact Nylon.
- Chemical Resistant.
- Barbed to hold hose without clamps.
- Colors may vary.

JT&T's Vacuum Hose Connectors are made of specially compounded nylon, designed not to deteriorate or split from heat & ozone under the hood. Excellent oil, grease & chemical resistance. Connectors are barbed on all sides to hold hose without clamps. In addition to vacuum line, they can be used for: windshield washers, power antennas, defrosters, headlight vacuum systems, power seats, power windows & as emissions fittings for almost any automotive vacuum job.

2-Way Straight Connectors (Couplers)

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4822H	1/8" (All Sides)	1 Barb (All Sides)	Yellow	2
4822F	1/8" (All Sides)	1 Barb (All Sides)	Yellow	25
4822	1/8" (All Sides)	1 Barb (All Sides)	Yellow	50
4823H	3/16" (All Sides)	1 Barb (All Sides)	Black	2
4823F	3/16" (All Sides)	1 Barb (All Sides)	Black	25
4823	3/16" (All Sides)	1 Barb (All Sides)	Black	50
4824H	1/4" (All Sides)	1 Barb (All Sides)	Black	2
4824F	1/4" (All Sides)	1 Barb (All Sides)	Black	25
4824	1/4" (All Sides)	1 Barb (All Sides)	Black	50
4825H	3/8" (All Sides)	1 Barb (All Sides)	Black	2
4825F	3/8" (All Sides)	1 Barb (All Sides)	Black	25
4825	3/8" (All Sides)	1 Barb (All Sides)	Black	50
4826H	1/8" x 1/4"	2 Barbs(1/8") x 1 Barb(1/4")	Black	2
4826F	1/8" x 1/4"	2 Barbs(1/8") x 1 Barb(1/4")	Black	25
4826	1/8" x 1/4"	2 Barbs(1/8") x 1 Barb(1/4")	Black	50



3-Way (T) Connectors

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4816H	1/8" (All Sides)	2 Barbs (All Sides)	White	2
4816F	1/8" (All Sides)	2 Barbs (All Sides)	White	25
4816	1/8" (All Sides)	2 Barbs (All Sides)	White	50
4817H	3/16" (All Sides)	2 Barbs (All Sides)	White	2
4817F	3/16" (All Sides)	2 Barbs (All Sides)	White	25
4817	3/16" (All Sides)	2 Barbs (All Sides)	White	50
4818H	1/4" (All Sides)	1 Barb (All Sides)	White	2
4818F	1/4" (All Sides)	1 Barb (All Sides)	White	25
4818	1/4" (All Sides)	1 Barb (All Sides)	White	50
4819H	3/8" (All Sides)	1 Barb (All Sides)	Black	2
4819F	3/8" (All Sides)	1 Barb (All Sides)	Black	25
4819	3/8" (All Sides)	1 Barb (All Sides)	Black	50



Additional Nylon Vacuum Connector Products continued on page 97.

Caps/Grommets/Connectors

3-Way (Y) Connectors

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4832H	3/16" (All Sides)	1 Barb (All Sides)	Black	2
4832F	3/16" (All Sides)	1 Barb (All Sides)	Black	25
4832	3/16" (All Sides)	1 Barb (All Sides)	Black	50
4833H	1/4" (All Sides)	1 Barb (All Sides)	Neon Green	2
4833F	1/4" (All Sides)	1 Barb (All Sides)	Neon Green	25
4833	1/4" (All Sides)	1 Barb (All Sides)	Neon Green	50
4834H	1/4" x 1/4" x 3/16"	1 Barb (All Sides)	Neon Green	2
4834F	1/4" x 1/4" x 3/16"	1 Barb (All Sides)	Neon Green	25
4834	1/4" x 1/4" x 3/16"	1 Barb (All Sides)	Neon Green	50
4836H	1/4" x 3/8" x 3/8"	1 Barb (All Sides)	Black	2
4836F	1/4" x 3/8" x 3/8"	1 Barb (All Sides)	Black	25
4836	1/4" x 3/8" x 3/8"	1 Barb (All Sides)	Black	50
4837H	3/8" (All Sides)	1 Barb (All Sides)	Black	2
4837F	3/8" (All Sides)	1 Barb (All Sides)	Black	25
4837	3/8" (All Sides)	1 Barb (All Sides)	Black	50



4-Way Connector

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4830H	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	2
4830F	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	15
4830	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	50



5-Way Connector

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4831H	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	2
4831F	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	15
4831	3/16" (All Sides)	1 Barb (All Sides)	Neon Green	50



Universal 2-Way Straight Connector (Coupler)

- Ends can be cut off to fit 1/8", 1/4" or 3/8" size vacuum hose.

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4820H	Universal	2 Barbs (All Sides)	Black	2
4820F	Universal	2 Barbs (All Sides)	Black	15
4820	Universal	2 Barbs (All Sides)	Black	50



Universal 3-Way (T) Connector


- Ends can be cut off to fit 1/8", 1/4" or 3/8" size vacuum hose.

Part#	Ordering Size Outer Diameter	Barb(s)	Color	Pcs
4821H	Universal	2 Barbs (All Sides)	Black	2
4821F	Universal	2 Barbs (All Sides)	Black	15
4821	Universal	2 Barbs (All Sides)	Black	50



Grommets

- **A = Bore Diameter**
- **B = Groove Width**
- **C = Outside Diameter**
- **D = Overall Thickness**
- **E = Groove Diameter (Mounting Hole)**



JT&T's Grommets are collared on each side to keep them in place & are generally made of vinyl, rubber or PVC. Grommets are commonly used whenever wires pass through drilled holes, punched sheet metal, plastic casings, etc., to prevent abrasion & cushion vibration. If metal or another hard surface has a hole made in it, the hole may have sharp edges. Electrical wires, cord, rope, lacings or other soft vulnerable material passing through the hole can become abraded, cut or electrical insulation may break due to repeated flexing at the exit point. Grommets are used to avoid this & also protect the wiring from contamination via dirt, air, water, etc. The smooth, soft inner surface of the grommet shields the wire from damage.

Part #	Ordering Size	Color	Pcs	A	B	C	D	E
4400H	1/4"	Black	18	1/8"	1/16"	11/32"	3/16"	1/4"
4400L	1/4"	Black	50	1/8"	1/16"	11/32"	3/16"	1/4"
4400C	1/4"	Black	100	1/8"	1/16"	11/32"	3/16"	1/4"
4401H	5/16"	Black	15	3/16"	1/16"	7/16"	7/32"	5/16"
4401L	5/16"	Black	50	3/16"	1/16"	7/16"	7/32"	5/16"
4401C	5/16"	Black	100	3/16"	1/16"	7/16"	7/32"	5/16"
4402H	3/8"	Black	13	1/4"	1/16"	9/16"	1/4"	3/8"
4402L	3/8"	Black	50	1/4"	1/16"	9/16"	1/4"	3/8"
4402C	3/8"	Black	100	1/4"	1/16"	9/16"	1/4"	3/8"
4403H	7/16"	Black	12	5/16"	1/16"	5/8"	1/4"	7/16"
4403L	7/16"	Black	50	5/16"	1/16"	5/8"	1/4"	7/16"
4403C	7/16"	Black	100	5/16"	1/16"	5/8"	1/4"	7/16"
4404H	1/2"	Black	11	3/8"	1/16"	5/8"	1/4"	1/2"
4404L	1/2"	Black	50	3/8"	1/16"	5/8"	1/4"	1/2"
4404C	1/2"	Black	100	3/8"	1/16"	5/8"	1/4"	1/2"
4405H	5/8"	Black	7	1/2"	1/16"	13/16"	9/32"	5/8"
4405L	5/8"	Black	50	1/2"	1/16"	13/16"	9/32"	5/8"
4405C	5/8"	Black	100	1/2"	1/16"	13/16"	9/32"	5/8"
4406H	21/32"	Black	5	25/64"	1/8"	27/32"	3/8"	21/32"
4406L	21/32"	Black	50	25/64"	1/8"	27/32"	3/8"	21/32"
4406C	21/32"	Black	100	25/64"	1/8"	27/32"	3/8"	21/32"
4407H	7/8"	Black	4	5/8"	1/16"	1-1/8"	9/32"	7/8"
4407L	7/8"	Black	50	5/8"	1/16"	1-1/8"	9/32"	7/8"
4407C	7/8"	Black	100	5/8"	1/16"	1-1/8"	9/32"	7/8"
4408H	1"	Black	4	11/16"	1/16"	1-5/16"	3/8"	1"
4408L	1"	Black	50	11/16"	1/16"	1-5/16"	3/8"	1"
4408C	1"	Black	100	11/16"	1/16"	1-5/16"	3/8"	1"
4409H	1-3/8"	Black	2	1"	1/8"	1-3/4"	1/2"	1-3/8"
4409L	1-3/8"	Black	50	1"	1/8"	1-3/4"	1/2"	1-3/8"
4409C	1-3/8"	Black	100	1"	1/8"	1-3/4"	1/2"	1-3/8"

4450H - Assorted Black Grommets | 13 Pcs.

- 1/4" thru 3/8" Groove Diameter (Mounting Hole).



Part#	Description	Pcs
4400	1/4" Mounting Hole Grommets	5
4401	5/16" Mounting Hole Grommets	4
4402	3/8" Mounting Hole Grommets	4

Kit is in a re-closable container.

4451H - Assorted Black Grommets | 9 Pcs.

- 7/16" thru 5/8" Groove Diameter (Mounting Hole).



Part#	Description	Pcs
4403	7/16" Mounting Hole Grommets	3
4404	1/2" Mounting Hole Grommets	3
4405	5/8" Mounting Hole Grommets	3

Kit is in a re-closable container.

4452H - Assorted Black Grommets | 5 Pcs.

- 21/32" thru 1-3/8" Groove Diameter (Mounting Hole).




Part#	Description	Pcs
4406	21/32" Mounting Hole Grommets	2
4407	7/8" Mounting Hole Grommets	1
4408	1" Mounting Hole Grommets	1
4409	1-3/8" Mounting Hole Grommets	1

Kit is in a re-closable container.

4453H - Assorted Black Grommets | 15 Pcs.

- 1/4" thru 7/8" Groove Diameter (Mounting Hole).



Part#	Description	Pcs
4400	1/4" Mounting Hole Grommets	2
4401	5/16" Mounting Hole Grommets	2
4402	3/8" Mounting Hole Grommets	2
4403	7/16" Mounting Hole Grommets	2
4404	1/2" Mounting Hole Grommets	2
4405	5/8" Mounting Hole Grommets	3
4406	21/32" Mounting Hole Grommets	1
4407	7/8" Mounting Hole Grommets	1

Kit is in a re-closable container.